



NOTES

1. SIGN COMBINATION AND MINIMUM SIGN MOUNTING HEIGHT SHALL DETERMINE POST LENGTH. A 10' (MIN.) POST SHALL BE USED. A COMBINATION OF SIGNS GREATER THAN 36" IN HEIGHT SHALL REQUIRE A 12' (MIN.) POST.
2. SIGN POST SIZING SHALL BE BASED ON OREGON STANDARD DRAWING TM681 (PERMANENT PERFORATED STEEL SQUARE TUBE TABLE - 85 MPH). THE MINIMUM POST SIZE SHALL BE 2" X 2" 12-GA. SQUARE TUBE. IF SIGN PANEL AREA IS GREATER THAN THAT ALLOWED BY A 2.5" X 2.5" 12-GA. SQUARE TUBE, THEN A 2.5" X 2.5" 10-GA. SQUARE TUBE POST SHALL BE USED, WITH A SLIP BASE FOUNDATION PER OREGON STANDARD DRAWING TM688.
3. SIGN POSTS IN CONCRETE AREAS SHALL BE INSTALLED ON SURFACE-MOUNTED BREAKAWAY BASES.
4. NYLON SPACERS SHALL BE USED TO PREVENT CONTACT BETWEEN GALVANIZED STEEL AND ALUMINUM MATERIAL SURFACES.

<i>REVISION</i>	<i>DATE</i>	<i>BY</i>	DEPARTMENT OF TRANSPORTATION AND DEVELOPMENT 150 BEAVERCREEK ROAD OREGON CITY, OR 97045		APPROVAL DATE: 6/1/2020	SCALE: N.T.S.	STANDARD DRAWING
REV 1	11/19	BP			SIGN MOUNTING AND ATTACHMENTS	T150	
REVISION	3/20	RM					