


GENERAL NOTES

1. ALL WORK AND MATERIALS SHALL CONFORM TO THESE PLANS AND THE APPLICABLE PROVISIONS OF THE CLACKAMAS COUNTY ROADWAY STANDARDS. IMPROVEMENTS DEPICTED ON THESE PLANS ARE IN CONFORMANCE WITH COUNTY LAND USE ACTION CASEFILE _____. (INSERT PLANNING FILE NUMBER, EXAMPLE- Z0123-03-D).
2. IN ORDER TO PROTECT UNDERGROUND FACILITIES, EXCAVATORS PERFORMING THE WORK SET FORTH ON THESE PLANS MUST COMPLY WITH THE PROVISIONS OF ORS 757.557 (REQUIRES CONTRACTOR TO NOTIFY THE OREGON UTILITY NOTIFICATION CENTER AT LEAST 48 HOURS, BUT NO MORE THAN 10 BUSINESS DAYS, PRIOR TO ANY EXCAVATION).
3. THE LOCATION OF EXISTING UTILITIES SHOWN ON THE PLANS IS APPROXIMATE AND SHOWN FOR INFORMATION PURPOSES ONLY. THE CONTRACTOR SHALL HAVE ALL UTILITIES LOCATED PRIOR TO COMMENCING CONSTRUCTION. NOTIFY ENGINEER AND DTD, ENGINEERING OF ANY DISCREPANCIES PRIOR TO CONSTRUCTION. ADDITIONAL UNDERGROUND UTILITIES MAY EXIST.
4. VERTICAL DATUM: (INSERT BENCH MARK ELEVATION).
5. TOPOGRAPHIC SURVEY BY: (INSERT LICENSED SURVEYOR'S OR ENGINEER'S COMPANY AND NAME).
6. TRENCHES WITHIN THE RIGHTS-OF-WAY SHALL BE BACKFILLED WITH LOW STRENGTH CONTROLLED DENSITY FILL (CDF) WHEN:
 - TRENCHES ARE WITHIN THE ROADWAY OF ALL ARTERIALS AND COLLECTOR CLASSIFIED ROADS;
 - THE AFFECTED ROADWAY SURFACE IS NEWER THAN FIVE (5) YEARS FROM THE TIME OF THE LAST OVERLAY, WITHOUT REGARD TO THE ROADWAY CLASSIFICATION;
 - DEEMED NECESSARY BY THE COUNTY ROAD OFFICIAL.

WHEN TRENCHES ARE EXEMPT FROM USE OF CDF THE ROADWAY TRENCH SHALL BE BACKFILLED WITH AN APPROVED GRANULAR MATERIAL CONFORMING TO ODOT/APWA CLASS B SPECIFICATIONS. SEE SECTION 311 AND 312 OF THE CLACKAMAS COUNTY UTILITY REGULATION FOR SPECIFICATIONS, LOCATED WITHIN COUNTY CODE.
7. TRENCHES OUTSIDE OF RIGHTS-OF-WAY MAY BE BACKFILLED IN ACCORDANCE WITH NATIVE MATERIAL AND COMPACTION SPECIFICATIONS FOR ODOT/APWA CLASS A BACKFILL.
8. VEGETATION AND TOPSOIL ARE TO BE STRIPPED TO MINERAL EARTH (AND INSPECTED BY THE COUNTY) PRIOR TO PLACEMENT OF FILL OR BASE MATERIALS.
9. IN ADDITION TO ANY REQUIRED COMPACTION TESTING, THE COUNTY REQUIRES A PROOF ROLL WITH A FULLY LOADED 10-YARD DUMP TRUCK TO CHECK SUBGRADE COMPACTION PRIOR TO PLACEMENT OF ROCK SUBBASE AND AGAIN AT THE COMPLETION OF THE PLACEMENT OF THE BASE ROCK PRIOR TO PAVING THE FIRST LIFT OF ASPHALT CONCRETE.
10. ASPHALTIC CONCRETE MIX IS TO BE BATCHED FROM A MIX FORMULA APPROVED BY OSHD FOR MATERIAL USED. PAVING CONTRACTOR SHALL PROVIDE A CERTIFICATE OF COMPLIANCE FROM ASPHALT PAVEMENT PLANT.
11. SUBSEQUENT SETTLEMENT OR CRACKING OF FINISHED SURFACE WITHIN THE WARRANTY PERIOD SHALL BE CONSIDERED TO BE A FAILURE OF THE SUBGRADE AND REPAIRED AT NO COST TO THE COUNTY AND IN A MANNER ACCEPTABLE TO THE COUNTY.
12. THE CONTRACTOR SHALL CONTROL TRAFFIC THROUGH THE PROJECT SITE IN CONFORMANCE WITH THE LATEST EDITION OF THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, AND OREGON SUPPLEMENTS. THE CONTRACTOR SHALL, AT ALL TIMES, MAINTAIN LOCAL ACCESS FOR EMERGENCY VEHICLES, BUSINESSES, BUSES, AND HOMEOWNERS ALONG THE PROJECT SITE.
13. THE CONTRACTOR AND/OR SUB-CONTRACTOR SHALL HAVE A MINIMUM OF ONE (1) SET OF APPROVED CONSTRUCTION PLANS ON THE JOB SITE AT ALL TIMES DURING THE CONSTRUCTION PHASES.
14. CONTRACTOR SHALL REMOVE AND DISPOSE OF TREES, STUMPS, BRUSH, ROOTS, TOPSOIL AND OTHER MATERIAL ENCOUNTERED DURING THE CONSTRUCTION OF THE ROADWAY AND WHERE INDICATED ON THE PLANS. MATERIAL SHALL BE DISPOSED OF IN ACCORDANCE WITH LOCAL, REGIONAL AND STATE REGULATIONS AT FACILITIES AUTHORIZED TO ACCEPT SUCH MATERIAL. CONTACT THE CLACKAMAS COUNTY COMMUNITY ENVIRONMENT SECTION AT 503-742-4400 FOR DISPOSAL OPTIONS.
15. CONTRACTOR SHALL COORDINATE AND SCHEDULE ALL EARTHWORK, TRENCH BACKFILL AND ROAD CONSTRUCTION COMPACTION TESTS, AND GEOTECHNICAL REVIEWS WITH THE SOILS TESTING LAB AS REQUIRED FOR ACCEPTANCE OF PROJECT WORK BY CLACKAMAS COUNTY.

<i>REVISION</i>	<i>DATE</i>	<i>BY</i>	DEPARTMENT OF TRANSPORTATION AND DEVELOPMENT 150 BEAVERCREEK ROAD OREGON CITY, OR 97045		APPROVAL DATE: 2/1/13	SCALE: N.T.S.	STANDARD DRAWING
EDIT SPACING	12/12	RN			STANDARD NOTES GENERAL	N100	