


NOTES

1. TURNAROUND CAN BE ON EITHER SIDE OF STREET.
2. TURNAROUND SHALL BE A MINIMUM OF 20 FEET WIDE OR THE WIDTH OF THE ROAD, WHICHEVER IS GREATER.
3. CURBS ON PUBLIC AND COUNTY ROADS SHALL BE MARKED YELLOW WITH 4" THERMOPLASTIC. CURBS ON PRIVATE ROADS SHALL BE PAINTED RED AND BE POSTED WITH NO PARKING SIGNAGE ON ALTERNATE SIDES OF ROADWAY, 50' ON CENTER.
4. IF NO CURBS ARE PRESENT, STREETS SHALL BE POSTED WITH NO PARKING SIGNAGE ON ALTERNATE SIDES OF ROADWAY, 50' ON CENTER.

<i>REVISION</i>	<i>DATE</i>	<i>BY</i>	DEPARTMENT OF TRANSPORTATION AND DEVELOPMENT		<i>APPROVAL DATE:</i> 2/1/13	<i>SCALE:</i> N.T.S.	STANDARD DRAWING
TEXT NOTE 3	12/12	RN			150 BEAVERCREEK ROAD OREGON CITY, OR 97045	PASSENGER VEHICLE TURNAROUND	
TEXT NOTE 4	12/12	RN					